



DIMENSIONS:

Load Capacity: 350 lbs.

EXTERIOR

Height - 32"
Width - 42"
Depth - 27"

INTERIOR

Height - 17 1/2"
Depth - 14"
Rack to Glass - 1 7/8"
Rack Width - 13 7/8"
Rack Units - 10 RUs

SHIPPING BOX (Palletized)

Length - 48"
Width - 40"
Height - 51"
Ship Weight - 230 lbs



Available for immediate shipping



Ask about customized design
and prototype capabilities

The GMP-200S is a 32" tall cart that holds a single display up to 42". Comes standard with 10RU 19" rack mount bracket in front and rear, 6 port APC® surge protector, adjustable shelf and has an interior depth of 14". Includes universal screen mounting system and set-top camera mount (TT-1).

Please include model number of screen when ordering.

GMP - 200S - TT1

SOLID STEEL CARTS

The most **FEATURES** on the market:

- ▶ One adjustable interior rack mounted shelf
- ▶ 6 Port APC surge protector
- ▶ Cable management features
- ▶ Tempered, tinted locking front glass door
- ▶ Bolted rear panel for easy access to equipment
- ▶ Standard 19" front and rear rack mount brackets, 10RUs of space
- ▶ Standard adjustable v/c camera platform
- ▶ 32" Height for optimal face to face communication
- ▶ Standard 4" double truck ball bearing casters, two with brake
- ▶ 100% Solid steel construction

Choose your **OPTIONS:**

- ▶ Additional rack mount shelf (US-1)
- ▶ Rack mounted M-Audio® speaker module (PSM-200)
- ▶ Heavy duty 6" caster upgrade
- ▶ Single gang Wall Plates (3 RCA, VGA+Audio and VGA+Audio+LAN)
- ▶ GM-9000 to accommodate deeper equipment
- ▶ 6 Port rack mount APC® surge protector (RCK-PWR)
- ▶ Custom cut Rack Shelf for Lifesize®, Polycom® and Tandberg® codecs
- ▶ Revolabs® Shelving System in various configurations for wireless microphone integration



Furniture Engineered For Today's Technology